### Case Studies









## **Specifications**


art Number	KD2.6	KD(O)3.9
ixel pitch	2.6mm	3.9mm
ED type	SMD1515	SMD1415/1921
esolution of module	96*96	64*64
ensity(dots/m²)	118336	65536
abinet material	Die-casting aluminum	Die-casting aluminum
ize of cabinet(mm)	500*500*87	500*500*87
leight of cabinet	8.5KG	8.5KG
laintenance Method	Back Service	Back Service
upport curve or not	Yes	Yes
fax power consumption	600W/m <sup>2</sup>	750W/m <sup>2</sup>
verage power consumption	200W/m <sup>2</sup>	250W/m <sup>2</sup>
olors	16.7M	16.7M
ray scale	16bits	16bits
olor temperature	6500-9000K	6500-9000K
efresh frequency	≥3840Hz	≥3840Hz
rightness	900cd/m²	4500cd/m <sup>2</sup>
rightness control	256grade	256grade
grade	IP30	IP65

Multiple angles can be selected: 0°±5°±10°±15°±22.5°





Mixed structural splicing for improved utilization KU,RD, KM, KU, KS



One Cabinet can Realize S Shape, Concave/Convex Curves with Single Cabinet.



### **Cylindrical Splicing**

8 Cabinets Form 1 Circle, Just 1.2m in Diameter. Free Curved Surface, Innovative curve lock system high precision, easy adjustment





The best solution for curved rental screens



# **KD SERIES**

INDOOR AND OUTDOOR APPLICATION







# **Product Advantages**

Optimized Bottom Gap Design


Four-corner Protection with a Unique Design

Effortless and Rapid Installation Process


Weight







Thickness



#### Flexible installation

Modular design

Quick installation, convenient and flexible, supporting multiple installation methods.









Lightking Tech Group Co., Ltd.

www.lightking-led.com

Building A, Zhongsheng Industrial Park, No. 4 Lixin Road, Bao'an District, Shenzhen, China

TEL: +86-755-81467007 E-mail: service1@lightking.hk

Twitter: @lightkingLED

Facebook: Lightking Tech Group Co., Ltd.

Youtube: @LightkingLED

Linkedin: Lightking Tech Group Co., Ltd.







